



- Drafts
 - BRS:
 - BRS:
- Pending
- Active
 - L1: (527) backlightS3 and S2shaped and lamp and electr
 - L2: (175) 1 and (CCFL or (cold near2 cathode))
 - L3: (137) 2 and ("315"/S.ccls. or "362"/S.ccls. or "313"/S
- Failed
- Saved
- Favorites
- Tagged (0)
- UDC
- Queue
- Trash

DBs US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB

Default operator: OR

☒ Plurals☒ Highlight all hit terms initially

	Type	L #	Hits	Search Text	DBs	Time Stamp	Comments	Er	Erro
1	BRS	L1	527	backlightS3 and S2shaped and lamp and electrode and ((high and low) near3 (voltage or electrode))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 09:09			
2	BRS	L2	175	1 and (CCFL or (cold near2 cathode))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 09:09			
3	BRS	L3	137	2 and ("315"/S.ccls. or "362"/S.ccls. or "313"/S.ccls. or "349"/S.ccls.)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 09:10			